


## UTP Category 5E Cables

Content of Data Sheet				
Product model	CAB-LC2100B-E-IN			
Product specification	HSYV-5e 4x2x0.45			
Test Standard	ISO/IEC11801 、 TIA-568-C.2、 IEC61156-6			
Conductor	Material	OFC(Oxygen free copper)		
	AWG	25		
	Nom.O.D.(mm)	0.45±0.005 mm		
	DC resistance	≤115 Ω/km		
Insulation	Material	HDPE		
	Thickness	0.17±0.01 mm		
	Diameter	0.81±0.05 mm		
	Color	Blue/White- Blue	Green/White-Green	
		Orange /White-Orange	Brown/White-Brown	
Pitch	Offset pitch	≤25 mm		
	Cable pitch	≤140 mm		
Sheath	Material	PVC(complies RoHS/REACH)		
	External O.D.	4.7±0.3 mm		
	Color	Gray(RAL7046)		
	Tensile strength	>13.5 Mpa		
	Thickness	0.55±0.05 mm		
Surface Printing	Letter height	3.0±0.3 mm		
	Color	Black		
	Print error & Space	1±0.005 m		
	Case number	Yes		



Packing	Packing	Carton
	Once packing dimension	340mm*220mm*340mm
	Twice packing dimension	360mm*470mm*360mm
	Twice packing quantity	2 cases
Packing length	305±1 m	
Rip-cord	Yes	
Ambient temperature	-20°C ~ 60°C	

**Zhejiang Uniview Technologies Co.,Ltd.**

Building No.10, Wanlun Science Park, Jiangling Road 88, Binjiang District, Hangzhou, Zhejiang, China

Email: [overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)

<http://www.uniview.com>

©2011-2018 Zhejiang Uniview Technologies Co.,Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.