

DNS

Support TR069, NAT
DMZ, DNS features



Support Multiple SSID



Support Multiple VLAN



Support Easy-Mesh



Support IPV6 , PPPoE, DHCP
and Static IP configuration for
WAN Interface



Support IP, MAC filtering, -
Firewall Functionality in
routed mode



Support for XPON, adaptive
EPON or GPON OLT on the
network



RH804GW-DG
GPON ONT

1. Product Overview

RH804GW-DG terminal devices are designed for fulfilling FTTH and triple play service demand of fixed network operators or cable operators. The box is based on the mature Gigabit GPON technology, which have high ratio of performance to price, and the technology of 802.11 n/ac WiFi , Wireless power can reach more than 23dBm, Layer 2/3. They are highly reliable and easy to maintain, with guaranteed QoS for different service. And It is fully compliant with technical regulations such as ITU-T G.984.x and technical requirement of GPON Equipment.



2. Interface of device.1

Parameter	Nominal
Connector style	SC/APC OR SC/UPC
PON quantity	1
Fiber style	Single mode
Wavelength	TX: 1310 +/-20nm RX: 1490 +/-10nm
PON interface standard	ITU-T G.984.2/ITU-T G.984.3/ITU-TG.988 Class B+
PON interface receiving rate	2.488Gpbs
PON interface transmitting rate	1.244Gpbs
Output optical power	Min: 0.5dBm Max: +5dBm
Optical receiver sensitivity	Precede -28dBm
The length of the optical link	Max 20km

3 WIFI Specifications

Standard	IEEE 802.11 ac/b/g/n
Frequency	2412-2472MHz 5GHz: Band-1 frequency 5.15GHz ~ 5.25GHz Band-2 frequency 5.25GHz~5.35GHz Band-3 frequency 5.500GHz ~ 5.700GHz Band-4 frequency 5.725GHz ~ 5.825GHz
Transmission speed	2.4GHz Frequency IEEE 802.11b : 11/5.5/2/1M(Auto) IEEE 802.11g: 54/48/36/24/18/12/9/6(Auto) IEEE 802.11n: 270/243/216/162/108/81/54/27Mbps, up to 300Mbps 5GHz Frequency IEEE 802.11n: Highest transmission speed up to 300Mbps IEEE 802.11ac : Highest transmission speed up to 867Mbps
Channel number	2.4GHz : 13 5GHz: 4 (It depends on the actual area.)
Spread-spectrum Technique	DSSS(Direct sequence spread spectrum)
Data Modulation	DBPSK . DQPSK . CCK and OFDM(BPSK/QPSK/16-QAM/64-QAM)
Sensitivity @PER (Packet Error Rate)	270M: -68dBm@10% PER; 130M: -68dBm@10% PER 108M: -68dBm@10% PER; 54M: -68dBm@10% PER 11M: -85dBm@8% PER; 6M: -88dBm@10% PER 1M: -90dBm@8% PER
Transmission Distance	Indoor Maximum 120 meter, Outdoor Maximum 360 meters (The distance depends on the environment)
RF power (2.4GHz)	20dBm EIRP
RF power (5 GHz)	Band-1 EIRP 17.45dBm Band-2 EIRP 17.82dBm Band-3 EIRP 17.92dBm Band-4 EIRP 18.92dBm
Antenna	5dBi Antennas

4. Specification and working environment

Parameter	Nominal
Dimension	176mm×112mm×31mm(L×W×H)
Net weight	0.35kg
Typical power consumption	<8W
Noise	None

Parameter	Nominal
Cooling style	Naturally cooling
Power supply	12V, 1.0Amp
Installation style	Support PC, wall mount or put inside of information box
Environment	5-50 °C
Atmospheric pressure	70-106Kpa
MTBF	50,000hours@25 °C
MTTR	30minutes
Parameter	Nominal

a. Special function

- Support TR069,NAT,DMZ,DNS features
- Support Multiple ssid
- Support Multiple VLAN
- Support MU-MIMO
- Support Easy-Mesh
- Support IPV6
- PPPoE
- DHCP and Static IP configuration for WANInterface
- Support IP
- MAC filtering, Firewall Functionality in routed mode
- Support for XPON
- Adaptive EPON or GPON OLT on the network

5. Interface of device.2

Port Type	Function
PON port	Connect PON port with internet by SC type, single mode optical fiber cable
LAN 1-4 port	RJ45 Port connects to local internet,4 GE port

6. Network Mode

