

F702-S

Fingerprint Access Control Terminal



Just on touch! That's all it takes for accessing control to ZK Software's F702-S biometric reader. It offers the flexibility to be installed standalone or with any third party panels that support 26-bit Wiegand. Fast, reliable performance and the affordability strengthen ZK reader's competitive edge. Each reader has the capacity to store up to 2,200 fingerprint

templates and 50,000 transactions. Enrolling users is fast and easy, Since most of our readers have a user-friendly keypad and display, enrolling users is fast and easy. All our readers are easily accessed. Together with a TCP/IP or a serial port, the readers can update and synchronize automatically.

Feature


- Equipped with durable and recognizable ZK optical sensor
- 1-touch 1-second employee recognition
- Store up to 2200 templates and 5000 transactions
- · Enter PINs is not necessary
- Support 50 time zones, 5 groups and 10 unlock combinations
- · Tamper-proofed switch and alarm output

- Request-to-exit and alarm contacts
- Standalone operation without a computer
- TCP/IP, Serial and Wiegand Interfaces
- Export real time 1-touch data to 3rd party hosted or non-hosted applications
- Indicate audio-visual signals for acceptance or rejection due to valid or invalid fingerprints
- SDK available for OEM customers and software developers


Specifications

| Fingerprint Capacity | 2,200 templates |
|------------------------------|---|
| Transaction Capacity | 50,000 |
| Hardware Platform | ZEM500 |
| Sensor | ZK Optical Sensor |
| Algorithm Version | ZK Finger v9.0 |
| Communication | RS232/485, TCP/IP, USB-host |
| Access Control Interface for | 3 rd party electric lock, door sensor, exit button, alarm, DoorBell |
| Standard Functions | SMS, DLST, Webserver, Workcode, Anti-passback |
| Optional Functions | ID, Mifare, HID, Scheduled-Bell, 9 digit user ID, Self-Service Query, Automatic Status Switch, Soap, printer |
| Wiegand Signal | Input & Output |
| Display | B & W LCD Screen |
| Power Supply | 12V DC |
| Operating Temperature | 0°C - 45°C |
| Operating Humidity | 20% - 80% |
| Dimension(WxHxD)mm | 140.5×116×43.5 |
| Gross Weight | 0.85kg |

Configuration



Dimensions (mm)



ZKTeco Inc.

ZK Mansion, Wuhe Rd, Gangtou, Bantlari, Buji Town, Longgang District, Shenzhen China 518129 Tel: 86-755-8960 2345/46/47/48 E-mail: sales@zkteco.com www.zkteco.com Global Offices:

USA: + 1 732-412-6007 EU: +34 916532891 Brazil: +55 31 2515-8326 Thalland: +66-027199154 Mexico: +52-55-52928418 South Africa: +77 12 259 1047 Egypt: +201110444134 Dubai: +971 4 6091 310 India: +91 8123536788

India: +91 8123536788 Indonesia: +62 21 2921 8949 Vietnam: +84-0169-5813007 Philippines: +63-9084118832 Russla: +8-915-178-46-81

